

Extraordinary



Federal Republic of Nigeria

Official Gazette

No. 142

Lagos - 26th December, 2014

Vol. 101

Government Notice No. 225

The following is published as supplement to this *Gazette* :

<i>S.I. No.</i>	<i>Short Title</i>	<i>Page</i>
64	National Environmental (Air Quality Control) Regulations, 2014	B827-850

Printed and Published by The Federal Government Printer, Lagos, Nigeria
FGP 154/102015/300

Annual Subscription from 1st January, 2015 is Local : ₦25,000.00 Overseas : ₦37,500.00 [Surface Mail]
₦49,500.00 [Second Class Air Mail]. Present issue ₦2,000.00 per copy. Subscribers who wish to obtain *Gazette* after
1st January should apply to the Federal Government Printer, Lagos for amended Subscriptions.

**NATIONAL ENVIRONMENTAL STANDARDS AND
REGULATIONS ENFORCEMENT AGENCY
(ESTABLISHMENT) ACT, 2007**

**NATIONAL ENVIRONMENTAL (AIR QUALITY CONTROL)
REGULATIONS, 2014**



ARRANGEMENT OF REGULATIONS

Regulation :

PART I—GENERAL PROVISIONS

1. Purpose.
2. Scope.
3. Application.

PART II—EMISSIONS FROM STATIONERY SOURCES

4. Prohibition of Installations.
5. Accidental Discharge of Pollutants.
6. Maximum Air Contaminants Concentrations.
7. Prohibition of Two Stroke Engines.
8. Metals and Metallic Compounds.
9. Information on Emission of Criteria Pollutants.
10. Pollution Abatement Technologies.
11. Stack Specifications.
12. Prohibition to Burn.
13. Environmental Impact Assessment (EIA) and Environmental Management Plan (EMP).

PART III—EMISSIONS FROM MOBILE SOURCES

14. Categories of Mobile Sources of Emission.
15. Emissions from Vehicles.
16. Conflict Resolution.
17. Two-Stroke Engine Ban.

**PART IV—CONTROL OF INDOOR AIR POLLUTION IN OFFICES,
PUBLIC PLACES AND HOMES**

18. Maximum Concentrations in Offices and Public Places.
19. Maximum Concentrations in Homes.
20. Building Requirements.
21. Banned Pesticides.
22. Power Generating Sets.
23. Provision of Exhaust Chimney.

- 24. Prohibition of Smoking.
PART V—EMISSIONS FROM OTHER SOURCES—FUEL ADDITIVES, ETC.
- 25. Fuel Additives.
- 26. Control of Fugitive Particulate Matter.
- 27. Ozone Depleting Substances (ODS) Alternatives.
- 28. Agrochemicals Handling.
- 29. Renewable Energy.
- 30. Quarrying Operations.
- 31. Mining Operations.

PART VI—AMBIENT AIR QUALITY STANDARDS

- 32. Operations of Industrial Plants or Facilities.
- 33. Ambient Air Quality Standards.

PART VII—CONTROL OF ODOUR

- 34. Control of Odour.
- 35. Odour Detection Threshold.

PART VIII—ENFORCEMENT

- 36. Enforcement Notices.
- 37. Enforcement of Notice Reminder.
- 38. Power to Enter and Seal Facility or Premises.

PART IX—PERMIT

- 39. Permit.

PART X—OFFENCES AND PENALTIES

- 40. Offences and Penalties.

PART XI—MISCELLANEOUS PROVISIONS

- 41. Interpretation.
- 42. Citation.

SCHEDULES

S. I. No. 64 of 2014

**NATIONAL ENVIRONMENTAL STANDARDS AND
REGULATIONS ENFORCEMENT AGENCY
(ESTABLISHMENT) ACT, 2007**

**NATIONAL ENVIRONMENTAL (AIR QUALITY CONTROL)
REGULATIONS, 2014**

In exercise of the powers conferred on me by section 34 of the National Environmental Standards and Regulations Enforcement Agency (Establishment) Act, 2007 and all other powers enabling me in that behalf, I, MRS LAURENTIA LARABA-MALLAM, Honourable Minister of Environment, hereby make the following Regulations—

[9th Day of December, 2014]

Commence-
ment.

PART I—GENERAL PROVISIONS

1. The purpose of these Regulations is to provide for—

Purpose.

(a) for improved control of the nation's air quality to such an extent that would enhance the protection of flora and fauna, human health, and other resources affected by air quality deteriorations.

(b) all users, the right to—

(i) clean air ;

(ii) utilize and benefit from all natural resources managed according to the principles of sustainable development ;

(iii) be informed of the nature and extent of the potential hazard of any activity, undertaking or project and to be served timely notice of any significant rise in the level of pollution and the accidental or deliberate release into the atmosphere of harmful or hazardous substances ; and

(c) the clean-up and rehabilitation of the affected area.

2. The Scope of these Regulations includes provision for—

Scope.

(a) maximum permissible limit values for certain pollutants in the air, avoid, prevent or reduce harmful effects on the environment and human health ;

(b) the assessment and minimization of emissions from point, area and line sources ;

(c) adequate information on emissions, ambient air concentrations of pollutants in the air, as well as air quality trends spatially and temporary ; and

(d) measures to enhance improvements in emissions and ambient air quality.

3. These Regulations shall apply to Point, Mobile and Area sources of air pollution, as well as Indoor and Ambient air quality control.

Application.

PART II

EMISSIONS FROM STATIONARY SOURCES

Prohibition
of
Installations.

4.—(1) Except with the written approval of the Agency, a person shall not install a new equipment as described in Schedule I to these Regulations, within the premises or facilities situate within an area designated as a residential zone having demarcated boundaries which appear in the gazetted local plan prepared by the appropriate local planning authorities ;

(2) In the absence of gazetted local plan described in sub-regulation (1) of this regulation, the premises shall mean such facilities situate at least 100 meters to the nearest dwelling house within the housing estate.

Accidental
Discharge of
Pollutants.

5. Where any accidental, emergency or unauthorized release or discharge of a contaminant into the air occurs, the person responsible for the release or discharge shall within 24 hours inform the Agency in writing as prescribed in Schedule II to these Regulations.

Maximum
Air
Contaminants
Concentration.

6. A person shall not discharge contaminants into the air from an industrial source, fuel-burning equipment and others higher than the concentrations prescribed in Schedules III, IV, V and VI to these Regulations.

Prohibition
of Two-
Stroke
Engines.

7. A person shall not import fuel-combustion equipment of any kind with two-stroke engine into the country.

Metals and
Metallic
Compounds.

8. A person trading or operating an industry or process, in which fuel-burning equipment or industrial plant is used for the heating of metals leading to emissions of particulate matter, shall ensure that the concentration at any point in-stack of particulate matter shall not exceed the standards prescribed in Schedules V and VI to these Regulations.

Information
on
Emissions of
Criteria
Pollutants.

9. A person operating an industrial plant or facility shall forward to the Agency information related to its point source emissions for criteria pollutants annually, within 3 months of the end of the calendar year.

Pollution
Abatement
Technologies.

10. A person shall install air pollution control device to new equipment, installations or retrofit an existing facility with technology or technologies that enable that facility to meet the national air quality emissions standards.

Stack
Specifications.

11. A person operating an industrial infrastructure emitting pollutants into the atmosphere shall channel each point of discharge into the atmosphere through stacks that meet Good Engineering Practice (GEP) stack height and complies with stack specification prescribed under Schedule VII to these Regulations.

12. A person shall not burn or permit to burn standing biomass within its premises or neighbourhood, except where it is authorized in accordance with the National Environmental (Control of Bush or Forest Fire and Open Burning) Regulations, 2011.

Prohibition
to Burn.

13. A person shall in accordance with the Environmental Impact Assessment Act—

Environmental
Impact
Assessment
and
Environmental
Management
Plan.

(a) carry out an Environmental Impact Assessment (EIA) for new projects or modification including expansion of existing ones before commencement of activity in accordance with the Environmental Impact Assessment Act ;

(b) submit Environmental Audit Report (EAR) for existing infrastructure on a three yearly basis or as may be required by the Agency ; and

(c) submit an Environmental Management Plan (EMP) for any project as may be required by relevant Laws.

PART III—EMISSIONS FROM MOBILE SOURCES

14. Mobile sources shall be categorized in accordance with the provisions of Schedule VIII to these Regulations.

Categories of
Mobile
Sources of
Emission.

15. Emissions from road vehicles shall be in accordance with the provisions of the National Environmental (Control of Vehicular Emissions from Petrol and Diesel Engines) Regulations, 2011, other extant Regulations and as provided in Schedules IX and X to these Regulations.

Emission
from
Vehicles.

16. The Agency shall have the sole responsibility to resolve conflicts arising from multiple provisions in standards stipulated under extant Regulations.

Conflict
Resolution.

17. As from the commencement of these Regulations, a person shall not manufacture, assemble or import Two Stroke Engines of any kind for use in Nigeria.

Two Stroke
Engine Ban.

PART IV

CONTROL OF INDOOR AIR POLLUTION IN OFFICES, PUBLIC PLACES AND HOMES

18. The maximum concentrations of indoor air contaminants for offices and public places shall conform to the limits prescribed under Schedule XI to these Regulations.

Maximum
Concentrations
in Offices
and Public
Places.

19. The maximum concentrations for indoor air contaminants for homes shall conform to the limits prescribed in Schedule XII to these Regulations.

Maximum
Concentrations
in Homes.

Building
Requirements.

20. A person shall ensure that the ventilation system in a building facilitates improved air quality and is designed in accordance with the extant building code of the relevant national regulating authority.

Banned
Pesticides

21. Banned pesticides under the provisions of the National Environmental (Control of Hazardous Chemicals and Pesticides) Regulations, 2014 and other extant Regulations shall not be used indoors.

Power
Generating
Sets.

22.—(1) A power generating set shall not be positioned within the building where it can cause health hazard to the occupants.

(2) A power generating set shall be positioned in such a way that the flue gases—

(a) are discharged or drawn back into the building or the building ventilation system ; and

(b) do not become a nuisance to the inhabitants of any building or the neighbourhood.

Provision of
Exhaust
Chimney.

23. Every building especially homes and offices with cooking facilities shall have exhaust chimney to channel out the flue gases outside the indoor environment.

Prohibition
of Smoking

24. Smoking in public places is prohibited, except in designated area.

**PART V—EMISSIONS FROM OTHER SOURCES, FUEL
ADDITIVES, ETC.**

Fuel
Additives.

25. A person—

(a) shall use fuel additives as may be provided by the appropriate regulatory authority ;

(b) granted a licence to manufacture, process or trade in any fuel additive shall not import, sell, offer for sale or introduce into commerce such fuel additive unless the same has been registered with the appropriate authority ; and

(c) shall not introduce any proposed fuel additive that would in any way increase emissions of any of the regulated gases prescribed in Schedule IX to these Regulations.

Control of
Fugitive
Particulate
Matter.

26. A Person shall—

(a) not allow or permit the emission of any fugitive particulate matter in excess of the levels prescribed in Schedule X to these Regulations ; and

(b) maintain the maximum limit values for evaporative and refueling emissions from gasoline vehicles prescribed in Schedule X to these Regulations.

- | | |
|--|---|
| 27. The National Environmental (Ozone Layer Protection) Regulations, 2009 shall apply in the importation, handling, storage, sale and use of alternatives to Ozone Depleting Substances (ODS). | Ozone
Depleting
Substances
Alternatives. |
| 28. The importation, handling, storage, transportation and use of chemicals and agrochemicals shall be in accordance with the extant laws and Regulations. | Agro-
Chemicals
Handling. |
| 29. A person operating a renewable energy generating plant shall ensure that the plant does not exceed the permissible limits as contained in extant laws and Regulations. | Renewable
Energy. |
| 30. A person engaged in quarrying operations shall carry out such operation in accordance with the National Environmental (Quarrying and Blasting Operations) Regulations, 2013 and other extant Regulations. | Quarrying
Operations. |
| 31. A person engaged in mining operations shall carry out such operations in accordance with the National Environmental (Mining and Processing of Coal Ores and Industrial Minerals) Regulations, 2009 and other extant Regulations. | Mining
Operations. |

PART VI—AMBIENT AIR QUALITY STANDARDS

- | | |
|---|---|
| 32. A person operating an industrial plant or facility shall forward to the Agency any information which the Agency deems appropriate regarding its operations. | Operations
of Industrial
Plants or
Facilities. |
| 33. A person undertaking a business or activity releasing emissions into ambient air shall ensure that the ambient air quality within its premises or operational areas associated with emissions from own facilities do not exceed 60% of the ambient air quality standard prescribed in Schedule XIII to these Regulations, without prejudice to the contributions emanating from other facilities to its premises. | Ambient Air
Quality
Standards. |

PART VII—CONTROL OF ODOUR

- | | |
|--|----------------------------------|
| 34. A person shall not emit or allow the emission of noxious and foul odorous substances to reach nuisance threshold levels within its neighbourhood such that not more than 5% of the population will experience annoyance greater than 5% of the time per month up to three continuous months. | Control of
Odour. |
| 35. A person shall not release or cause the emission of malodorous substances beyond the detection thresholds as prescribed in Schedule XIV to these Regulations. | Odour
Detection
Threshold. |

PART VIII—ENFORCEMENT

Enforcement
Notices.

36.—(1) An enforcement notice shall be served where the Agency is of the opinion that an operator has contravened, is contravening or is likely to contravene any condition of a permit.

(2) An enforcement notice shall specify the—

(a) activities or matters constituting the contravention or making it likely that the contravention will arise, as the case may be ;

(b) steps that must be taken to remedy the contravention or to remedy the activities or matters making it likely that the contravention will arise ; and

(c) period within which those steps must be taken.

(3) The provisions of sub-regulation (2) (a) of this regulation shall apply whether or not the particular manner of operating the facility in question, is regulated by or contravenes a condition of the permit.

(4) An officer of the Agency may, in the course of his duty under these Regulations, at any reasonable time—

(a) enter and search any premises or facility to carry out air emission testing, take samples or specimen for analysis, and measurements in length and of level of standards to which these Regulations relate ; and

(b) seize and detain for such time as may be necessary for the purpose of these Regulations any article by means of or in relation to which he believes any provision of these Regulations has been contravened.

Enforcement
of Notice
Reminder.

37.—(1) Where a person fails to comply with the enforcement notice within the specified period given under Regulation 36 (2) of these Regulations, a second notice shall be served.

(2) Where a person fails to comply with the second reminder of the enforcement notice within the specified time limit, the Agency shall issue a suspension notice, seal the facility or premises or take any other punitive action as may be necessary.

(3) Where a suspension notice is served pursuant to these Regulations, the permit shall, on the service of such notice cease to have effect as stated in the notice.

(4) The Agency may withdraw a suspension notice after verification of compliance.

Power to
enter and
Seal facility
or Premises.

38. The Agency shall have the power to enter and seal any facility or premises found contravening any of the provisions of these Regulations.

PART IX—PERMIT

39. The Agency shall issue permits for air quality control in accordance with the provisions of the National Environmental (Permitting and Licensing System) Regulations, 2009. Permit.

PART X—OFFENCES AND PENALTIES

40. A person who violates any of the provisions of these Regulations commits an offence and shall on conviction— Offences and Penalties.

(a) be liable to a fine of not less than one hundred thousand Naira or to imprisonment for a term not less than 6 months or to both, such fine and imprisonment and an additional fine of not less than ₦10,000.00 for every day the offence subsists for individual offenders ; and

(b) where the offence is committed by a body corporate, be liable to a fine not less than ₦1,000,000.00 and additional fine of ₦50,000.00 for every day the offence subsists.

PART XI—MISCELLANEOUS PROVISIONS

41. In these Regulations, unless the context otherwise requires— Interpretation.

“*Act*” means the Act establishing the Agency ;

“*Agency*” means National Environmental Standards and Regulations Enforcement Agency (NESREA) ;

“*Air*” means the mixture of gases that envelop the Earth, known as the atmosphere and comprising Nitrogen (78%), Oxygen (21%), Argon, Hydrogen and other gases (about 1%) ;

“*Air Pollutant*” means “*pollutants*” (as defined in these Regulations), emitted into or formed in the Earth’s atmosphere ;

“*Air pollution*” includes the state of increased concentration of substances in the atmosphere which has or has the potential of adversely affecting the health of any living substance, ecosystem, natural or built environment, at a level that exceeds the carrying capacity of the atmospheric removal mechanisms to return the air to its natural background concentrations for such substances ;

“*Air Quality*” means an index of the healthiness of the air based on the quantity of polluting substances it contains. Air is considered safe when its harmful chemical contents are below the standards considered safe for plants, animal and human habitation as well as the physical infrastructure within it ;

“*Ambient Air*” means planetary boundary layer or the troposphere (outdoor air) in which humans and other organisms live and breathe ;

“*Background Air Concentrations*” means “*clean air*”, as defined in this regulation ;

"Building" means permanent or temporary structure constructed with exterior walls and a roof, all attached facilities required for human habitation as residential or for businesses, commercial, recreational, and industrial ;

"Clean Air" means the air whose regulated pollutant concentrations are below that specified in the ambient air quality standards in these Regulation ;

"Court" means the Federal or State High Court ;

"Emission" means the quantity of air contaminant discharged from a known source into the atmosphere over a specified time ;

"Emission Reduction Technology" means the technologies used as scrubbers or as part of improved operational process to reduce emissions from any facility ;

"Enforcement Notice" Letters of Compliance Concerns or Abatement notices informing a person of observed violations and the need to remedy the same within a time limit, failure of which a person shall be sanctioned as provided in these Regulations ;

"EIA" means Environmental Impact Assessment ;

"EMP" means Environmental Management Plan ;

"Fuel-combustion Equipment" means any device used for the combustion of fuel in which heat is transferred from the products of combustion indirectly for the production of useful heat or power ;

"Flue Gas" means combustion or process related gases containing pollutants emitted directly into the atmosphere by small, medium or large scale industrial production or for the provision of services such as electricity generation, among others ;

"Fugitive Emission" means pollutants discharged into the atmosphere from sources other than combustion or production processes but related to general processes such as evaporation, frictional processes leading to wears, system leakages, in a stationary area or line source ;

"Hazardous Substances" mean those substances which present short-term acute hazards such as acute toxicity by ingestion, inhalation or skin absorption, corrosiveness or other skin or eye contact hazard or the risk of fire explosion or long-term toxicity upon repeated exposure ;

"Indoor Air" means the air inside a building including mobile homes, offices, commercial and residential homes ;

"Installations" mean the whole of a system of machineries and accessories set up and arranged to produce goods and services, and leading to the emission of pollutants into the atmosphere ;

"Key Sources" (for any pollutant) means a group of sources contributing up to the total pollutant emissions in the locality, state or nation ;

"Mechanical Ventilation" means controlled air circulation within an indoor space using motorised mechanical systems to improve on the natural air circulation capability provided for in the building design ;

"Mobile Source" includes sources such as road, air, railway and navigational vehicles, which emit pollutants into the atmosphere during locomotion ;

"Odour" means the property of a substance that gives it a characteristics scent or smell. Odour assessment, properties include intensity, detestability, character and hedonic tone, which is the perceived pleasantness or unpleasantness ;

"Odour Detectability" means the minimum concentration of odour emitting substances that produce an olfactory response or sensation ;

"Ozone Depleting Substances (ODS)" includes the wide range of compounds now known as chlorofluorocarbons (CFCs), chemically inert (non-toxic, non-combustible, physically very stable under high ranges of temperature and pressure, neither oxidized nor photo-dissociated in the lower atmosphere), are easily converted from liquid to gaseous states at ordinary temperatures, and which became very useful as refrigerants in air conditioning and refrigeration equipment, but later found to become photo-dissociated in the stratosphere to release chlorine radicals, which reacts strongly with stratospheric Ozone (O_3), converting it to Oxygen (O and O_2) atoms, and finally resulting in the depletion (reduction in the concentration) of stratospheric ozone leading to ground penetration of UV-B radiation, absorbed by stratospheric ozone and protecting human health from UV-B radiation ;

"Particulate Matter" means contaminants in solid and liquid phases in suspension in the atmosphere ;

"Pasting" means the Posting of a notice at the address of the owner or occupant of the Premises or facility ; or the putting of a notice in a public or conspicuous place so that people including those the notice is meant for, can see it ;

"Person" means a legal entity including an individual, association, corporate body, organization, government, government agency, institution that own facility or facilities which emit pollutants into the atmosphere ;

"Point Source" means a single source emissions into the atmosphere, contributing not less than 500 metric tonnes of CO , or 100 metric tonnes of any of NO , SO_2 and PM into the atmosphere during full operational annual cycle ;

"Pollution Control Device" means any infrastructure designed for use mainly as scrubbers to reduce the concentration of pollutants in their flue gas, thereby enhancing cleaner emissions from stacks of various air pollution sources ;

"Pollution Control Technology" means the technologies used in individual pollution control devices as defined in this Regulation ;

"Pollutant" means substances including gases, liquids, particulates, radioactive substances, biological materials, or other harmful chemicals or materials, noise or high energy radiation emitted into or formed in any part of the Earth's subsystems (atmosphere, lithosphere or hydrosphere), with capacity to cause diseases or death to humans and ecosystems; or likely to cause damage to any living organisms or to the natural or built environment ;

"Public places" means building or other facilities owned by government and organizations working for the overall interest of serving the society and established for the general use of the members of the public. They include government and private sector offices open to the public, hospitals and other healthcare facilities, commercial buildings, hotels, recreational facilities, public transport, amusement and entertainment facilities among others ;

"Radon" means an inert gas that does not readily interact with the body, but is usually released into buildings from the underlying soil ;

"Stationary Source" means any fixed (non-moving) facility such as power plants, petroleum refineries, petrochemical plants, process industries, etc associated with the production of goods and services, and leading to emissions of one or more types of pollutants into the atmosphere ;

"Tail Pipe" means the exhaust nozzle of a vehicle where the flue gases are released into the atmosphere ;

"Two-Stroke Engine" means an internal combustion engine which completes combustion within a single crankshaft, in an up (denoting fuel intake or compression) and down (denoting fuel combustion or exhaust) piston strokes ;

"Vehicle" means moving motorized means of locomotion propelled by a gasoline, diesel or other types of engines used as means of personal or public transport, or for movement of goods from place to place ;

"Ventilation" means the process of ensuring circulation of air within a building or any facility, which could be natural or motorized ;

"Volatile Organic Compounds (VOC)" mean organic compounds in gaseous state in the atmosphere, and usually divided broadly into methane (CH₄) and non-methane volatile organic compounds (NMVOC).

Citation.

42. These Regulations may be cited as the National Environmental (Air Quality Control) Regulations, 2014.

SCHEDULE I

NEW INSTALLATIONS WITHIN RESIDENTIAL AREAS NOT PERMITTED
WITHOUT PRIOR APPROVAL

[Regulation 4]

(a) Any equipment, plant or facility used for the purpose of heating or generating power that is rated to consume—

- (i) pulverised fuel ;
- (ii) any solid fuel at 20 kg or more per hour ; or
- (iii) any liquid or gaseous matter at 10 kg or Litre or more per hour.

(b) Any equipment, plant or facility that emits any solid particle exceeding 0.5kg per hour ;

(c) Any equipment, plant used for grain milling or polishing and consumes 1.5kw and above ;

(d) Any wood working machinery that consumes 0.75 kw and above ;

(e) Any equipment or facility used in the manufacture, packing or repacking of paints, varnishes, lacquers and all pesticides ;

(f) Any equipment, plant or facility used in the manufacture, packing or repacking of fish manure or animal feed or fertilizer ;

(g) Any equipment, plant or facility used in the manufacture, packing or repacking of industrial chemicals, in the process of which mercury, antimony, arsenic, cadmium, zinc, lead, copper, etc or any compound thereof is emitted ;

(h) Any equipment or plant used in the manufacture of asbestos containing products.

SCHEDULE II

PROCEDURE FOR REPORTING ACCIDENTAL DISCHARGE OF POLLUTANTS

[Regulation 5]

The information required includes the—

(a) date and time of the release or discharge ;

(b) duration of the release or discharge ;

(c) composition of the release or discharge showing—

(i) the concentration of air contaminants,

(ii) the emission rate, and

(iii) the total amount.

(d) description of the circumstances leading to the release or discharge ;

(e) steps and procedures taken to control the release or discharge, as well as those taken to prevent similar releases or discharges in the future ; and

(f) steps and procedures taken to clean up the release or discharge.

SCHEDULE III

POINT SOURCE MAXIMUM EMISSION LIMIT FOR FACILITIES AND PROCESS

[Regulation 6]

<i>Pollutants</i>	<i>Standard Applicable to Source</i>	<i>Maximum Permissible Limits (mg/Nm³)</i>	<i>Maximum Permissible Limits (ppm)</i>
1. Antimony and its Compounds.	Any Source	10 as Sb	2.0
2. Arsenic and its Compounds.	Any Source	10 as As	3.0
3. Cadmium and its Compounds.	Any Source	10 as Cd	2.0
4. Carbon Monoxide	Any industrial Source	500 as CO	400
5. Copper and its Compounds.	Any industrial source	100 as Cu	36
6. Hydrofluoric Acids and Fluoride Compounds.	Any source other than the manufacture of Aluminium from Alumina.	50 as HF	56
7. Hydrogen Sulfide	(i) Geothermal Power Plants	a, b	5.0
	(iii) Any source other than (i) and (ii)	7 as H ₂ S	
8. Lead	Any trade, industry or process.	10 as Pb	1.1
9. Mercury	Any Source	5 as elemental Hg	0.6
10. Nickel and its compounds, except Nickel Carbonyl ^c	Any Source	20 as Ni	8
11. NO _x	(i) Manufacture of Nitric Acid	2,000 as acid and NO _x and calculated as NO ₂	975
	(ii) Fuel burning steam generators		
	Existing Source	1,500 as NO ₂	730
	New Source	—	—

	• Coal-Fired	1,000 as NO ₂	487
	• Oil-Fired	500 as NO ₂	244
	(iii) Any source other than (i) and (ii)		
	Existing Source	1000 as NO ₂	487
	New Source	500 as NO ₂	244
12. Phosphorus Pentoxide	Any Source	200 as P ₂ O ₅	32
13. Zinc and its Compounds	Any Source	100 as Zn	34.2

Key :

- ^a — All new geothermal power plants starting construction by 01 January 2015 shall control H₂S emissions to not more than 150 g/GMW-Hr.
- ^b — All existing geothermal power plants shall control H₂S emissions to not more than 200 g/GMW-Hr within 5 years from the date of effectiveness of these Regulations.
- ^c — Emission limit of Nickel Carbonyl shall not exceed 0.5 mg/Ncm.

SCHEDEULE IV

STACK EMISSIONS FROM POINT SOURCES RELATED TO COMBUSTION

[Regulation 6]

Combustion Processes	Emission Standard					
	Flue Gas Concentration (kg TJ-Energy Consumed)					
	PM ₁₀	CH ₄	VOC	SO ₂	NO _x	CO
Public Electricity Generation :						
Coal	350	-	8	550	300	15
Heavy Fuel Oil (HFO)	1	15	0.1	2	190	0.6
Light Fuel Oil (LFO)	0.3	2	-	5	70	0.6
Natural Gas	0.1	1	2	0.5	110	1.0
Industrial Electricity Generation						
Coal	500	2	20	500	350	150
HFO	40	3	8	800	190	10
LFO	5	3	5	200	70	10
Natural Gas	0.1	1.4	5	0.5	110	10
Industrial Boilers/Heat Generation						
Fuel-wood	200	-	400	-	10	4000
Charcoal	200	-	400	-	10	4000
Commercial/Institutional Electricity/Heat Generation						
Fuel-wood	200	150	600	10	94	9000
Charcoal	150	100	400	10	75	4000
Coal	100	23	31	500	100	625
Chemical Process Industry						
Charcoal Kiln (kg/tonne)	1.24	-	2	-	0.112	1.6
Carbon Black (Stack) (kg/tonne)	6.7	-	77	0.045	6.2	123
Paint and Vanish (kg/tonne)	-	-	0.5	-	-	-
Plastics (kg/tonne)	-	-	5.9	-	-	-
Printing Ink (kg/tonne)	-	-	213	-	-	-
Soap and Detergents (kg/tonne)	7	-	-	-	-	-

SCHEDULE V

EMISSION STANDARDS FOR AIR POLLUTANTS FROM
INDUSTRIAL SOURCES/OPERATIONS

[Regulations 6 and 8]

<i>S/N</i>	<i>Pollutants¹</i>	<i>ppm</i>	<i>Averaging time (min.)</i>
1.	Ammonia	0.28	30
2.	Carbon Disulfide	0.01	30
3.	Chlorine and Chlorine Compounds expressed as Cl ²	0.03	5
4.	Formaldehyde	0.04	30
5.	Hydrogen Chloride	0.13	30
6.	Hydrogen Sulfide	0.07	30
7.	Nitrogen Dioxide	0.20, 0.14	30, 60
8.	Phenol	0.03	30
9.	Sulfur Dioxide	0.18, 0.13	30, 60

SCHEDULE VI

EMISSION LIMITS FOR SPECIFIC METAL POLLUTANT FROM STATIONARY SOURCES

[Regulations 6 and 8]

<i>No.</i>	<i>Substance</i>	<i>Limit (mg/m³)</i>
1.	Antimony	20-100
2.	Arsenic	20-100
3.	Cadmium	1.0-40
4.	Copper	20
5.	Lead	10-100
6.	Mercury	1.0-230
7.	Zinc	11.72

Source : Guidelines and Standards for Environmental Pollution Control in Nigeria.

SCHEDULE VII

INDUSTRIAL STACK HEIGHT REGULATION

[Regulation 11]

Industrial stacks shall comply with the Good Engineering Practice stack height (H_{GEP}), which ensures that emissions from the stack does not result in excessive concentrations of any air pollutant in the immediate vicinity of the sources, resulting from atmospheric downwash, eddies, or wakes which may be created by the source, nearby structures or terrain obstacles. For any industrial stack, the GEP Stack height shall be defined and calculated using the following relations :

$$H_{GEP} = H + 1.5L$$

Where H is the height of the adjacent structure or nearby structure, and L is the lesser dimension (height or maximum projected width of the adjacent or nearby structure or terrain).

A single representative stack may be used to represent several sources that are identified as "similar". "Similar stacks are those that are located within 100 m distance and emit the same pollutants, and have stack heights and flue gas exit velocities differ by less than 20%. The procedure for merging sources identifies one worst case representative stack from which all of the emission from the sources involved are modelled. The merged stack is typically located at the closest location, of all the stacks involved, to the property line. This location, if all other parameters were the same would result in the maximum modelled off-site concentration. Dissimilar stacks may be merged, by computing the parameter M for which stack, using :

$$M = \frac{(H_s V T_s)}{Q}$$

Where M is the parameter accounting for the relative influence of stack height, plume rise and emission rate on concentration,

H_s is the stack height, and

$$V \frac{\pi}{4} v^2 d^2$$

Where V is the stack gas volumetric flow rate (m^3/s), d is the stack exit internal diameter (m), v is the stack gas exit velocity (m/s), T_s is the stack gas exit temperature (K) and Q is the pollutant emission rate (g/s).

The stack with the lowest M value is used as the representative stack, so that the sum of emissions from all merged stacks is assumed to be emitted from the representative stack. The location of the representative stack is assumed to be the actual location closest to the property line. For dispersion modelling from multiple stack locations, the representative stacks would be used.

SHEDULLE VIII

SCHEDULE ON MOBILE SOURCE CLASSIFICATION

[Regulation 14]

<i>Mobile Source Grouping</i>	<i>Source Types</i>	<i>Definition of Source Type</i>
Air Transportation	Domestic and international Civil Aviation.	Emissions from all aircraft types excluding military.
Road Transportation	Passenger Cars.	Automobiles designated primarily for the transport of persons, having a capacity of 12 persons or less, or equipped with no special features such as four wheel drives or off-road operation. Maximum gross weight of 3900 kg.
	Passenger Cars with catalysts.	Passenger cars (as above) with 3-way catalysts for NOx control.
	Light Duty Trucks (LDT).	Automobiles designated primarily for the transport of cargo or equipped with special features such as four wheel drives or off-road operation. Maximum gross weight of 3900 kg.
	Light Duty Trucks with catalysts.	LDT (as above) with 3-way catalysts for NOx control.
	Heavy Duty Trucks and Buses (HDTB).	Any gasoline or diesel fuelled vehicles rated to exceed 3900 gross weight or designed to carry more than 12 persons at a time.
	Motorcycles.	Any vehicle designed to travel with not more than three wheels in contact with the ground, and weighing less than 680 kg.
Railways	All rail travelling vehicles.	Includes both passenger and freight coaches.
Water Transport	Internal Navigation.	All internal and coastal navigation, including small craft and fishing vessels not included under the International Marine Bunkers.
	International Marine Bunkers.	Sea going ships of all flags, including fishing vessels.
Other Non-Road Transportation	Lawn and Garden Equipment.	

	Agricultural Equipment. Logging Equipment. Light Commercial Equipment. Industrial Equipment. Construction Equipment. Airport Service Equipment.	
--	--	--

SCHEDULE IX

TAIL PIPE EMISSION STANDARDS FOR ROAD VEHICLES

[Regulations 15; 25(C)]

Mobile Source	Emission Standard									
	Tailpipe Concentration (%)					Emission Factor (g/km)				
	PM ₁₀	Soot	CO	NOX	VOC	PM ₁₀	Soot	CO	NOX	VOC
ROAD TRANSPORTATION										
Per Capita (PC)(Gasoline): [Fuel economy = 6.0 km/l]	-	-	-	-	-	-	-	13	1.6	1.2
PC (Gasoline) with catalysts : Fuel economy = 9.4 km/l	-	-	-	-	-	-	-	3.5	0.6	0.3
PC (Diesel): [Fuel economy = 6.8 km/l]	-	-	-	-	-	0.4	-	0.9	1.0	0.3
Light Duty Truck, LDT (Gasoline): [Fuel Economy = 5.1 k/l]	-	-	-	-	-	-	-	15	1.8	2.0
LDT (Gasoline) with Catalysts	-	25	-	-	-	-	-	10	1.0	0.8
LDT (Diesel)	-	40	-	-	-	0.5	-	8.0	1.2	0.45
Heavy Duty Truck, HDTB	-	40	-	-	-	0.9	-	9.0	12	2
Motorcycles/Tricycles	-	45	-	-	-	0.3	-	14	0.6	2.6

SCHEDULE X

FUGITIVE EMISSION STANDARDS FOR GASOLINE VEHICLES

[Regulations 15 ; 26(a)(b)]

<i>Fugitive Source</i>	<i>Pollutant</i>	<i>Emission Factor Standard (g/km)</i>
Tank Evaporative Emissions	VOC	0.45
Tank Refuelling Emissions	VOC	0.30

SCHEDULE XI

INDOOR AIR QUALITY FOR OFFICES AND PUBLIC PLACES

[Regulation 18]

<i>Parameter</i>	<i>Unit</i>	<i>8-hour average ^a</i>	
		<i>Excellent Class</i>	<i>Good Class</i>
Room Temperature	°C	20 to < 25.5	< 25.5
Relative Humidity	%	40 to < 70	< 70
Air movement	m/s	< 0.2	< 0.3
Carbon Monoxide (CO)	µg/m ³	< 2,000	< 10,000
	ppbv	< 1.7	< 8.7
Suspended Particulates (PM10)	µg/m ³	< 20	< 180
Nitrogen Dioxide (NO ₂)	µg/m ³	< 40	< 150
	ppbv	< 21	< 80
Ozone (O ₃)	µg/m ³	< 50	< 120
	ppbv	< 25	< 61
Formaldehyde (HCHO)	µg/m ³	< 30	< 100
	ppbv	< 24	< 81
Total Volatile Organic Compounds (TVOC)	µg/m ³	< 200	< 600
	ppbv	< 87	< 261
Radon (Rn)	Bq/m ³	< 150	< 200
Airborne Bacteria	cfu/m ³	< 500	< 1,000

Legends :

a. In some cases, it may not be practicable to take 8-hour continuous measurement. In these circumstances, surrogate measurement (i.e. an intermittent measurement strategy based on the average of half-an-hour measurements conducted at four time-slots) is also accepted.

SCHEDULE XII

MAXIMUM CONCENTRATIONS FOR INDOOR AIR CONTAMINANTS IN HOMES

[Regulation 19]

<i>S/N</i>	<i>Pollutants</i>	<i>Average Time</i>	<i>Limit for Acceptable indoor Air Quality</i>	<i>Unit</i>
1.	Carbon Monoxide (CO)	8hrs	10 9	mg/m ³ ppm
2.	Formaldehyde	8hrs	120 0.1	µg/m ³ ppm
3.	Ozone (O ₃)	8hrs	120 0.06	µg/m ³ ppm
4.	Total Volatile Organic Compound (TVOC)	8hrs	300	mg/m ³
5.	Respiratory Dust (<10 microns)	8hrs	150	mg/m ³
6.	Bacteria	8hrs	500	CFU/m ³ (algar plate)
7.	Fungi	8hrs	500	CFU/m ³ (algar plate)

SCHEDULE XIII
 AMBIENT AIR QUALITY STANDARDS

[Regulations 29, 30 and 33]

S/N	Pollutant	Time Weighted Average	Concentration in Ambient Air
1.	Sulphur dioxide (SO ₂)	Annual	80 µg/m ³
		24 hours	120 µg/m ³
		1 hour	350 µg/m ³
2.	Nitrogen dioxide (NO ₂)	Annual	80 µg/m ³
		24 hours	120 µg/m ³
		1 hour	200 µg/m ³
3.	Carbon monoxide (CO)	8 hours	5.0 mg/m ³
		1 hour	10 mg/m ³
4.	Particulate Matter (PM10)	Annual	60 µg/m ³
		24 hours	150 µg/m ³
5.	Ozone (O ₃)	8 hours	100 µg/m ³
		1 hour	180 µg/m ³
6.	Lead (Pb)	Annual	1.0 µg/m ³
		24 hours	1.4 µg/m ³
7.	Arsenic (As)	Annual	6,000 µg/m ³
8.	Nickel (Ni)	Annual	20,000 µg/m ³
9.	Cadmium (Cd)	Annual	5,000 µg/m ³
10.	Ammonia (NH ₃)	Annual	0.2 mg/m ³
		24 hours	0.6 mg/m ³

SCHEDULE XIV
AIR QUALITY STANDARD FOR SOME MALODOROUS COMPOUNDS

[Regulation 35]

<i>Substance</i>	<i>Chemical Formular</i>	<i>Irritation Threshold (ppmV)</i>	<i>Threshold Odour (ppmV)</i>	<i>Air Quality Standard for Odour (ppmV)</i>
Hydrogen Sulphide	H ₂ S	50-100	0.00001-0.8	5
Carbon Disulphide	CS ₂	-	0.21	0.1
Chlorine	Cl ₂	1-6	0.01-5.0	0.1
Ammonia	NH ₃	55-140	0.32-55	5
Benzene	C ₆ H ₆	-	468	50
Formaldehyde	HCHO	0.25-2.0	0.1-1.0	0.02
Methyl Mercaptan	CH ₃ SH	-	0.001-0.00026	0.0001
Ethyl Mercaptan	CH ₃ CH ₂ SH	-	0.00019-0.001	0.0001
Dimethyl Sulphide	(CH ₃) ₂ S	-	0.000048	-
Sulphur Dioxide	SO ₂	6-20	0.1-3.0	0.5

MADE at Abuja this 9th day of December, 2014.

MRS LAURENTIA LARABA MALLAM
Honourable Minister of Environment

EXPLANATORY NOTE

*(This Note does not form part of these Regulations
but is intended to explain its purport)*

These Regulations provide for improved control of the nation's air quality to enhance the protection of human health, flora and fauna, and other resources affected by air quality deterioration.